AGELESS MEDICAL NEW YORK 101 Lafayette Street, 6th floor, New York Telephone: 212-274-1705

21 inch I.3 ATA

Portable Hyperbaric Chamber



Solace²¹⁰

The most popular model in our Mild Hyperbaric Chamber line, the Solace 210 has a new look and added perks. With newly refined valve ports that raise the caliber of durability and safety, the upgraded sleek style of the Solace 210 combines function and elegance. Priced to be practical and designed to last, the Solace 210 responds to our fundamental goal - 'Making Hyperbarics Come to You'.

Main Body (bladder)

4psi (1.3ATA) operating pressure

Durable double-sided 44oz. urethane coated polyester weave material

Light & portable - folds for transport in its own carry bag

Dual air-exchange / regulator valves provide redundant pressure control

Patented 2-zipper seal facilitates self treatments

Extra large patient viewing windows

Larger external pass-through port





Inflation/Deflation valve allows both occupant and treatment administrator to control pressure



Dual redundant. air exchange valves maintain pressure and flush CO, out of the chamber

Occupant Observation

Three windows incorporated into urethane shell

Room light illuminates chamber

Direct audible communication with patient









Weights	LBS	KG
Bladder	27.0	12.2
Compressor	27.5	12.4
Bolsters	11.5	5.4
Mattress	11.0	5.2
Frame	18.0	8.2

Dimensions Chamber Inflated	Inches	Meters
Length	92.0	2.33
Diameter	22.0	0.56
Circumference	70.0	1.80

Volume 20.2ft3 0.572m3



OxyHealth chambers are manufactured in the USA in accordance with FDA, ASME, PVHO, NFPA, and GMP regulations and codes.

Chamber carry bag

Bolster set to cradle the chamber. Fabric covered foam construction matches chamber jacket.

Accessories

Chamber frame maintains form when deflated for ease of use and reduced inflation time.'

Mattress contoured to fit inside the chamber. Medical grade.

*Optional



Peripheral Equipment

10ft. medical grade hose with quick-disconnect couplings

Analog pressure gauge

High efficiency inline air filtration. Filters air to 0.01 microns!

Double head oil-less 1/4 hp compressors with dual air intake filters

